


Vakuum-Heißpresse

-1/+0,1 bar, Nutzraum Ø400x500mm, Presskraft 2900 kN, mit Beladesystem

Vacuum Hot Press

-1/+0,1 bar, useable space Ø400x500mm, Pressing force 2900 kN, with loading system



- präziser, steifer Pressrahmen mit geringer Verformung und exakter Führung des Pressstempels
- Verdichtungswegmessung und Verdichtungsgeschwindigkeitsmessung
- servohydraulische Kraftregelung - halbautomatisches Beladesystem
- Temperatur bis 2500°C - Temperaturkonstanz ± 10 K
- Kühldom zur Schnellkühlung
- precise, stiff press frame of little deformation and exact guidance of the press ram
- compression stroke measurement and compression speed measurement
- servo-hydraulic force control - semiautomatic loading system
- temperature up to 2500°C - temperature constancy ± 10 K
- cooling chamber for fast cooling

Member of the **SYS**TEC group

FCT

Anlagenbau GmbH



FCT Anlagenbau GmbH
Hönbacher Straße 10
D-96515 Sonneberg

Tel. +49 36 75 / 74 84 - 0
Fax +49 36 75 / 74 84 - 44

ISO 9001:2008 Certified
email: info@fct-anlagenbau.de
web: www.fct-anlagenbau.com

BLUECOMPETENCE
Alliance Member

Partner of the Engineering Industry
Sustainability Initiative